

# SAFETY DATA SHEET

Alloy SAC305 WS 483



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Alloy SAC305 WS 483  
**GHS reference number** : GHS141  
**Product description** : Not available.  
**Product type** : Solid: Paste  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Not applicable.

#### Uses advised against

Not applicable.

### 1.3 Details of the supplier of the safety data sheet

AIM  
9100 Henri Bourassa East  
Montreal, QC  
H1E 2S4  
(514) 494-2000

AIM Solder Europe Sp. z.o.o.  
ul. Papiernicza 7  
Łódź 92-312  
Poland

**e-mail address of person responsible for this SDS** : Safetydata@aimsolder.com

### 1.4 Emergency telephone number

**Telephone number** : INFOTRAC  
Europe: 0800-181-29-24  
International: (352) 323-3500

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319  
Repr. 1B, H360  
Aquatic Acute 1, H400  
Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Causes serious eye irritation.  
May damage fertility or the unborn child.  
Very toxic to aquatic life with long lasting effects.

### Precautionary statements

Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment.

Response : IF IN EYES: Rinse cautiously with water for several minutes. IF exposed or concerned: Get medical advice or attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name  | Identifiers   | %         | Classification                                   | Specific Conc. Limits, M-factors and ATEs | Type    |
|--|---|-----------|--|---|---------|
| Poly(oxy-1,2-ethanediyl), $\alpha$ -(1-oxooctadecyl)- $\omega$ -hydroxy- | CAS: 9004-99-3  | $\leq 10$ | Eye Irrit. 2, H319                               | -   | [1]     |
| silver   | REACH #:<br>01-2119555669-21<br>EC: 231-131-3<br>CAS: 7440-22-4 | $\leq 3$  | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | M [Acute] = 1000<br>M [Chronic] = 1000    | [1] [2] |
| 2-methylpentane-2,4-diol   | EC: 203-489-0<br>CAS: 107-41-5<br>Index: 603-053-00-3           | $\leq 3$  | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319        | -   | [1] [2] |

Alloy SAC305 WS 483

### SECTION 3: Composition/information on ingredients

|                                      |   |    |   |  |         |
|--------------------------------------|---|----|---|--|---------|
| bis(2-(2-methoxyethoxy) ethyl) ether | EC: 205-594-7<br>CAS: 143-24-8                                  | ≤3 | Eye Irrit. 2, H319<br>Repr. 1B, H360  | -                                      | [1]     |
| copper                               | REACH #:<br>01-2119480154-42<br>EC: 231-159-6<br>CAS: 7440-50-8 | ≤1 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | M [Acute] = 10000<br>M [Chronic] = 100 | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and materials for containment and cleaning up

**Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| E1       | 100 tonne                       | 200 tonne               |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name  | Exposure limit values   |
|--------------------------|---|
| silver                   | <b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b><br>TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction   |
| 2-methylpentane-2,4-diol | <b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b><br>STEL: 100 mg/m <sup>3</sup> 15 minutes. Form: vapor and inhalable fraction<br>TWA: 50 mg/m <sup>3</sup> 8 hours. Form: vapor and inhalable fraction |
| copper                   | <b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). [copper and its inorganic compounds]</b><br>TWA: 0.2 mg/m <sup>3</sup> , (calculated as Cu) 8 hours.   |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name  | Type | Exposure             | Value                  | Population         | Effects  |
|--------------------------|------|----------------------|------------------------|--------------------|----------|
| silver                   | DNEL | Long term Inhalation | 0.04 mg/m <sup>3</sup> | General population | Systemic |
|                          | DNEL | Long term Inhalation | 0.1 mg/m <sup>3</sup>  | Workers            | Systemic |
| 2-methylpentane-2,4-diol | DNEL | Long term Oral       | 1.2 mg/kg bw/day       | General population | Systemic |
|                          | DNEL | Long term Oral       | 1.5 mg/kg bw/day       | General population | Systemic |
|                          | DNEL | Long term Inhalation | 7.8 mg/m <sup>3</sup>  | General population | Systemic |
|                          | DNEL | Long term Dermal     | 15 mg/kg bw/day        | General population | Systemic |
|                          | DNEL | Long term Inhalation | 25 mg/m <sup>3</sup>   | General population | Local    |
|                          | DNEL | Long term Dermal     | 42 mg/kg bw/day        | Workers            | Systemic |
|                          | DNEL | Long term Inhalation | 44.4 mg/m <sup>3</sup> | Workers            | Systemic |

## SECTION 8: Exposure controls/personal protection

|                                     |      |                       |                      |                    |          |
|-------------------------------------|------|-----------------------|----------------------|--------------------|----------|
| bis(2-(2-methoxyethoxy)ethyl) ether | DNEL | Short term Inhalation | 49 mg/m <sup>3</sup> | General population | Local    |
|                                     | DNEL | Long term Inhalation  | 49 mg/m <sup>3</sup> | Workers            | Local    |
|                                     | DNEL | Short term Inhalation | 98 mg/m <sup>3</sup> | Workers            | Local    |
|                                     | DNEL | Long term Dermal      | 3 mg/kg bw/day       | Workers            | Systemic |
| copper                              | DNEL | Long term Inhalation  | 22 mg/m <sup>3</sup> | Workers            | Systemic |
|                                     | DNEL | Long term Oral        | 0.041 mg/kg bw/day   | General population | Systemic |
|                                     | DNEL | Short term Inhalation | 1 mg/m <sup>3</sup>  | General population | Local    |
|                                     | DNEL | Long term Inhalation  | 1 mg/m <sup>3</sup>  | General population | Local    |
|                                     | DNEL | Long term Dermal      | 137 mg/kg bw/day     | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 137 mg/kg bw/day     | Workers            | Systemic |
|                                     | DNEL | Short term Dermal     | 273 mg/kg bw/day     | General population | Systemic |
|                                     | DNEL | Short term Dermal     | 273 mg/kg bw/day     | Workers            | Systemic |

### PNECs

No PNECs available.

## 8.2 Exposure controls

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Solid. [Solder Paste]
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit** : Not applicable.
- Flash point** : Not applicable.
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : Not available.
- Viscosity** : Not applicable.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapor pressure** : Not available.
- Relative density** : Not available.
- Vapor density** : Not applicable.
- Explosive properties** : Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
- Oxidizing properties** : Not available.
- Particle characteristics**
- Median particle size** : Not available.



## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

| Product/ingredient name  | Result      | Species    | Dose        | Exposure |
|--|-------------|------------|-------------|----------|
| Poly(oxy-1,2-ethanediyl), $\alpha$ -(1-oxooctadecyl)- $\omega$ -hydroxy-2-methylpentane-2,4-diol | LD50 Oral   | Rat        | >20 g/kg    | -        |
|  | LD50 Oral   | Guinea pig | 2800 mg/kg  | -        |
|  | LD50 Oral   | Rabbit     | 3200 mg/kg  | -        |
|  | LD50 Oral   | Rat        | 3700 mg/kg  | -        |
|  | LD50 Oral   | Rat        | 3700 mg/kg  | -        |
| bis(2-(2-methoxyethoxy)ethyl) ether  | LD50 Dermal | Rat        | >6900 mg/kg | -        |
|  | LD50 Oral   | Rat        | 3850 mg/kg  | -        |

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

| Product/ingredient name             | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| 2-methylpentane-2,4-diol            | 3700         | N/A            | N/A                      | N/A                        | N/A                                 |
| bis(2-(2-methoxyethoxy)ethyl) ether | 3850         | N/A            | N/A                      | N/A                        | N/A                                 |

#### Irritation/Corrosion

| Product/ingredient name  | Result                   | Species | Score | Exposure        | Observation |
|--|--------------------------|---------|-------|-----------------|-------------|
| Poly(oxy-1,2-ethanediyl), $\alpha$ -(1-oxooctadecyl)- $\omega$ -hydroxy- | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 100 uL | -           |
|  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 uL | -           |
|  | Skin - Severe irritant   | Rabbit  | -     | 24 hours 500 uL | -           |
| 2-methylpentane-2,4-diol   | Skin - Mild irritant     | Rabbit  | -     | 465 mg          | -           |
|  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| bis(2-(2-methoxyethoxy)ethyl) ether                                      | Eyes - Mild irritant     | Rabbit  | -     | 500 mg          | -           |

**Conclusion/Summary** : Not available.

#### Sensitization

**Conclusion/Summary** : Not available.

#### Mutagenicity

## SECTION 11: Toxicological information

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

## SECTION 11: Toxicological information

Not available.

|                              |   |
|------------------------------|---|
| <b>Conclusion/Summary</b>    | : Not available.                                    |
| <b>General</b>               | : No known significant effects or critical hazards. |
| <b>Carcinogenicity</b>       | : No known significant effects or critical hazards. |
| <b>Mutagenicity</b>          | : No known significant effects or critical hazards. |
| <b>Reproductive toxicity</b> | : May damage fertility or the unborn child.         |

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name              | Result                                   | Species  | Exposure |
|--------------------------------------|--|--|----------|
| silver                               | Acute EC50 1.4 µg/l Marine water         | Algae - Chroomonas sp.   | 4 days   |
|                                      | Acute EC50 0.24 µg/l Fresh water         | Daphnia - Daphnia magna  | 48 hours |
|                                      | Acute LC50 11 µg/l Fresh water           | Crustaceans - Ceriodaphnia reticulata                                    | 48 hours |
| 2-methylpentane-2,4-diol             | Acute LC50 2.13 µg/l Fresh water         | Fish - Pimephales promelas   | 96 hours |
|                                      | Chronic NOEC 5 mg/l Marine water         | Algae - Glenodinium halli  | 72 hours |
|                                      | Acute EC50 2800000 µg/l Fresh water      | Crustaceans - Ceriodaphnia reticulata - Larvae                           | 48 hours |
| bis(2-(2-methoxyethoxy) ethyl) ether | Acute EC50 3200000 µg/l Fresh water      | Daphnia - Daphnia magna - Larvae   | 48 hours |
|                                      | Acute LC50 8000000 µg/l Marine water     | Fish - Alburnus alburnus   | 96 hours |
|                                      | EC10 2871 mg/l                           | Algae - Pseudokirchneriella subcapitata                                  | 72 hours |
| copper                               | EC50 8996 mg/l                           | Aquatic plants - Pseudokirchneriella subcapitata                         | 72 hours |
|                                      | EC50 7467 mg/l                           | Daphnia  | 48 hours |
|                                      | LC50 >5000 mg/l                          | Fish - Brachydanio rerio   | 96 hours |
|                                      | Acute EC50 1100 µg/l Fresh water         | Aquatic plants - Lemna minor   | 4 days   |
|                                      | Acute EC50 2.1 µg/l Fresh water          | Daphnia - Daphnia longispina - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours |
|                                      | Acute IC50 16 µg/l Fresh water           | Algae - Chlorella pyrenoidosa - Exponential growth phase                 | 72 hours |
|                                      | Acute IC50 5.4 mg/l Marine water         | Aquatic plants - Plantae - Exponential growth phase                      | 72 hours |
|                                      | Acute LC50 0.072 µg/l Marine water       | Crustaceans - Amphipoda - Adult  | 48 hours |
|                                      | Acute LC50 7.56 µg/l Marine water        | Fish - Periophthalmus waltoni - Adult                                    | 96 hours |
|                                      | Chronic NOEC 2.5 µg/l Marine water       | Algae - Nitzschia closterium - Exponential growth phase                  | 72 hours |
| Chronic NOEC 7 mg/l Fresh water      | Aquatic plants - Ceratophyllum demersum  | 3 days   |          |
| Chronic NOEC 0.02 mg/l Fresh water   | Crustaceans - Cambarus bartonii - Mature | 21 days  |          |
| Chronic NOEC 2 µg/l Fresh water      | Daphnia - Daphnia magna                  | 21 days  |          |
| Chronic NOEC 0.8 µg/l Fresh water    | Fish - Oreochromis niloticus -           | 6 weeks  |          |

## SECTION 12: Ecological information

Juvenile (Fledgling, Hatchling, Weanling)

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

| Product/ingredient name             | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------------------|--------------------|-----|-----------|
| silver                              | -                  | 70  | low       |
| 2-methylpentane-2,4-diol            | 0.58               | -   | low       |
| bis(2-(2-methoxyethoxy)ethyl) ether | -0.84              | -   | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                 | ADR/RID        | ADN            | IMDG           | IATA           |
|---------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number     | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name    | -              | -              | -              | -              |
| 14.3 Transport hazard class(es) | -              | -              | -              | -              |
| 14.4 Packing group              | -              | -              | -              | -              |
| 14.5 Environmental hazards      | No.            | No.            | No.            | No.            |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

| Intrinsic property    | Ingredient name                    | Status    | Reference number | Date of revision |
|-----------------------|------------------------------------|-----------|------------------|------------------|
| Toxic to reproduction | bis(2-(2-methoxyethoxy)ethyl)ether | Candidate | D(2020) 9139-DC  | 1/19/2021        |

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Restricted to professional users.

Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Listed

Ozone depleting substances (1005/2009/EU)

## SECTION 15: Regulatory information

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

| Category |
|----------|
| E1       |

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **15.2 Chemical Safety Assessment**

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification      |
|-------------------------|--------------------|
| Eye Irrit. 2, H319      | Calculation method |
| Repr. 1B, H360          | Calculation method |
| Aquatic Acute 1, H400   | Calculation method |
| Aquatic Chronic 1, H410 | Calculation method |

### Full text of abbreviated H statements

|      |   |
|------|---|
| H315 | Causes skin irritation.                               |
| H319 | Causes serious eye irritation.                        |
| H360 | May damage fertility or the unborn child.             |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |

### Full text of classifications [CLP/GHS]

|                   |   |
|-------------------|---|
| Aquatic Acute 1   | AQUATIC HAZARD (ACUTE) - Category 1             |
| Aquatic Chronic 1 | AQUATIC HAZARD (LONG-TERM) - Category 1         |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 |
| Repr. 1B          | TOXIC TO REPRODUCTION - Category 1B             |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2          |

**Date of printing** : 2/22/2023

**Date of issue/ Date of revision** : 2/22/2023

**Date of previous issue** : 2/22/2023

Alloy SAC305 WS 483

## SECTION 16: Other information

**Version** : 1.06

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.