

Material Safety Data Sheet

Alloy Sn46-Pb46-Bi8 NC 273LT



1. Product and company identification

Product name	: Alloy Sn46-Pb46-Bi8 NC 273LT
Synonym	: Not applicable
Material uses	: Industrial applications: Soldering, Electronics industry.
Manufacturer	: AIM 9100 Henri Bourassa East Montreal, QC H1E 2S4 (514) 494-2000 In the United States: AIM 25 Kenney Drive Cranston, RI 02920 (800) CALL-AIM
Validation date	: 10/14/2016
Print date	: 10/14/2016
<u>In case of emergency</u>	: INFOTRAC North America: (800) 535-5053 International: (352) 323-3500

2. Hazards identification

Emergency overview

Physical state	: Solid. [Metal alloy]
Color	: Silver-grey.
Odor	: Odorless.
Signal word	: WARNING!
Hazard statements	: HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
Precautionary measures	: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not ingest. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Use personal protective equipment as required. Wash thoroughly after handling.
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Ingestion	: Toxic if swallowed.
Skin	: Slightly irritating to the skin.
Eyes	: Slightly irritating to the eyes.

Potential chronic health effects

Chronic effects	: Can cause target organ damage.
Carcinogenicity	: Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.

2. Hazards identification

- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Target organs** : Causes damage to the following organs: kidneys, lungs, the reproductive system, digestive system, upper respiratory tract.
Contains material which causes damage to the following organs: the nervous system, spleen, brain, eye, lens or cornea.
Contains material which may cause damage to the following organs: blood, mucous membranes, peripheral nervous system, gastrointestinal tract, cardiovascular system, immune system, skin, bones, bone marrow, central nervous system (CNS).

Over-exposure signs/symptoms

- Inhalation** : No specific data.
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
irritation
watering
redness

- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
tin	7440-31-5	40 - 50
bismuth	7440-69-9	0.1 - 10
lead	7439-92-1	0.1 - 10
Rosin, hydrogenated	65997-06-0	0.1 - 10

Canada

Name	CAS number	%
tin	7440-31-5	40 - 50
lead	7439-92-1	0.1 - 10
bis(2-butoxyethyl) ether	112-73-2	0.1 - 10

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
lead	7439-92-1	Not regulated.	0.1 - 10	100 mg/m ³	2	0	0	-
bis(2-butoxyethyl) ether	112-73-2	UN1993	0.1 - 10	-	1	2	0	-
Rosin, hydrogenated	65997-06-0	Not regulated.	0.1 - 10	-	2	0	0	-
tin	7440-31-5	Not regulated.	40 - 50	100 mg/m ³	0	0	0	-

3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

- Flammability of the product** : No specific fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Massive metal is nonflammable.
- Special remarks on explosion hazards** : No additional remark.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
tin	<p>OSHA (United States, 0/1997). Notes: Respirable TWA: 2 mg/m³</p> <p>NIOSH (United States, 0/1994). Notes: Respirable TWA: 2 mg/m³ STEL: 4 mg/m³</p> <p>ACGIH TLV (United States, 3/2016). TWA: 2 mg/m³, (as Sn) 8 hours.</p> <p>NIOSH REL (United States, 10/2013). TWA: 2 mg/m³, (as Sn) 10 hours.</p>
lead	<p>ACGIH TLV (United States, 3/2016). TWA: 0.05 mg/m³, (as Pb) 8 hours.</p> <p>NIOSH REL (United States, 10/2013). TWA: 0.05 mg/m³ 8 hours.</p> <p>OSHA PEL (United States, 2/2013).</p>

8. Exposure controls/personal protection

TWA: 50 µg/m³, (as Pb) 8 hours.
OSHA PEL 1989 (United States, 3/1989).
 TWA: 50 µg/m³, (as Pb) 8 hours.

Canada

<u>Occupational exposure limits</u>		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	Notations
tin, as Sn	US ACGIH 3/2016	-	2	-	-	-	-	-	-	-	
	AB 4/2009	-	2	-	-	-	-	-	-	-	
tin	BC 5/2015	-	2	-	-	-	-	-	-	-	
	ON 7/2015	-	2	-	-	-	-	-	-	-	
	QC 1/2014	-	2	-	-	-	-	-	-	-	
	SK 7/2013	-	2	-	-	4	-	-	-	-	
lead, as Pb	US ACGIH 3/2016	-	0.05	-	-	-	-	-	-	-	
	AB 4/2009	-	0.05	-	-	-	-	-	-	-	
	BC 5/2015	-	0.05	-	-	-	-	-	-	-	
	ON 7/2015	-	0.05	-	-	-	-	-	-	-	
	QC 1/2014	-	0.05	-	-	-	-	-	-	-	
lead, measured as Pb	SK 7/2013	-	0.05	-	-	0.15	-	-	-	-	

Mexico

Occupational exposure limits

Ingredient	Exposure limits
tin	NOM-010-STPS (Mexico, 4/2016). LMPE-PPT: 2 mg/m ³ 8 hours.
lead	NOM-010-STPS (Mexico, 4/2016). LMPE-PPT: 0.05 mg/m ³ , (as Pb) 8 hours.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

8. Exposure controls/personal protection

- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

- Physical state** : Solid. [Metal alloy]
- Flash point** : [Product does not sustain combustion.]
- Color** : Silver-grey.
- Odor** : Odorless.
- Melting/freezing point** : 120 to 167°C (248 to 332.6°F)
- Relative density** : 9.35
- Dispersibility properties** : Not dispersible in the following materials: cold water, hot water, methanol, diethyl ether, n-octanol and acetone.
- Solubility** : Insoluble in the following materials: cold water.
- Aerosol product**

10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

United States

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bismuth	LD50 Oral	Rat	5000 mg/kg	-
Rosin, hydrogenated	LD50 Oral	Guinea pig	5000 mg/kg	-
	LD50 Oral	Rat	52 mg/kg	-
	LD50 Oral	Rat	8400 mg/kg	-

Conclusion/Summary : No additional remark.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

11. Toxicological information

Carcinogenicity

Conclusion/Summary : Overexposure to fumes may cause severe irritation to the respiratory tract, digestive system and to the eyes. Overexposure to tin oxide fumes may result in benign pneumoconiosis (stannosis). Repeated and prolonged contact may cause skin irritation or dermatitis. Repeated and prolonged contact may cause an allergic skin reaction (sensitization) in susceptible individuals.

Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
tin	-	-	-	-	-	None.
bismuth	-	-	-	-	-	None.
lead	-	2B	Reasonably anticipated to be a human carcinogen.	A3	-	None.
Rosin, hydrogenated	None.	4	-	-	-	-

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Canada

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis(2-butoxyethyl) ether	LD50 Oral	Rat	3900 mg/kg	-
	LD50 Oral	Rat	3900 mg/kg	-

Conclusion/Summary : No additional remark.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis(2-butoxyethyl) ether	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Overexposure to fumes may cause severe irritation to the respiratory tract, digestive system and to the eyes. Overexposure to tin oxide fumes may result in benign pneumoconiosis (stannosis). Repeated and prolonged contact may cause skin irritation or dermatitis. Repeated and prolonged contact may cause an allergic skin reaction (sensitization) in susceptible individuals.

Classification

11. Toxicological information

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
tin	-	-	-	None.	-	-
bismuth	-	-	-	None.	-	-
lead	A3	2B	-	None.	Reasonably anticipated to be a human carcinogen.	-
Rosin, hydrogenated	-	4	-	-	-	None.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Mexico

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis(2-butoxyethyl) ether	LD50 Oral	Rat	3900 mg/kg	-
	LD50 Oral	Rat	3900 mg/kg	-
Rosin, hydrogenated	LD50 Oral	Guinea pig	5000 mg/kg	-
	LD50 Oral	Rat	52 mg/kg	-
	LD50 Oral	Rat	8400 mg/kg	-

Conclusion/Summary : No additional remark.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Score	Score	Exposure	Observation
bis(2-butoxyethyl) ether	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Overexposure to fumes may cause severe irritation to the respiratory tract, digestive system and to the eyes. Overexposure to tin oxide fumes may result in benign pneumoconiosis (stannosis). Repeated and prolonged contact may cause skin irritation or dermatitis. Repeated and prolonged contact may cause an allergic skin reaction (sensitization) in susceptible individuals.

Classification

11. Toxicological information

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
tin	-	-	-	None.	-	-
bismuth	-	-	-	None.	-	-
lead	A3	2B	-	None.	Reasonably anticipated to be a human carcinogen.	-
Rosin, hydrogenated	-	4	-	-	-	None.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Other information

: To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp. - Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 4400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Over melting point, toxic metallic oxide fumes may be evolved.

Canada

Aquatic ecotoxicity

12. Ecological information

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp. - Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 4400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
bis(2-butoxyethyl) ether	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
	Acute LC50 134 mg/l Marine water	Crustaceans - Chaetogammarus marinus - Young	48 hours

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Over melting point, toxic metallic oxide fumes may be evolved.

Mexico

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp. - Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 4400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
bis(2-butoxyethyl) ether	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
	Acute LC50 134 mg/l Marine water	Crustaceans - Chaetogammarus marinus - Young	48 hours

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Over melting point, toxic metallic oxide fumes may be evolved.

Toxicity of the products of biodegradation : The products of degradation are more toxic than the product itself.

13. Disposal considerations







Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		Reportable quantity 190.48 lbs / 86.476 kg Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
TDG Classification	Not regulated.	-	-	-		-
Mexico Classification	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Reaction product of decanoic acid, 12-hydroxystearic acid and 1, 2-ethanediamine)	9	III	 	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Reaction product of decanoic acid, 12-hydroxystearic acid and 1, 2-ethanediamine)	9	III	 	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA-DGR Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Reaction product of decanoic acid, 12-hydroxystearic acid and 1, 2-ethanediamine)	9	III	 	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

PG* : Packing group

15. Regulatory information

United States

- HCS Classification** : Toxic material
Carcinogen
Target organ effects
- U.S. Federal regulations** : **TSCA 5(a)2 final significant new use rules:** bis(2-butoxyethyl) ether
TSCA 6 proposed risk management: lead
TSCA 8(a) PAIR: 2,2',2''-nitritotriethanol; 2,2'-iminodiethanol
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
TSCA 8(d) H and S data reporting: 2,2'-iminodiethanol: 1989
TSCA 12(b) one-time export: bis(2-butoxyethyl) ether
TSCA 12(b) annual export notification: lead
Commerce control list precursor: 2,2',2''-nitritotriethanol
Not determined.
Clean Water Act (CWA) 307: lead
Clean Water Act (CWA) 311: maleic acid; benzoic acid

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Immediate (acute) health hazard
Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
tin	40 - 50	No.	No.	No.	Yes.	No.
bismuth	0.1 - 10	Yes.	No.	No.	No.	No.
lead	0.1 - 10	No.	No.	No.	No.	Yes.
Rosin, hydrogenated	0.1 - 10	No.	No.	No.	Yes.	No.

SARA 313

15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	lead	7439-92-1	0.1 - 10
	bis(2-butoxyethyl) ether	112-73-2	0.1 - 10
Supplier notification	lead	7439-92-1	0.1 - 10
	bis(2-butoxyethyl) ether	112-73-2	0.1 - 10

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: TIN; LEAD

New York : The following components are listed: Lead

New Jersey : The following components are listed: TIN; LEAD; bis(2-butoxyethyl) ether

Pennsylvania : The following components are listed: TIN; LEAD COMPOUNDS; bis(2-butoxyethyl) ether

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
lead	Yes.	Yes.	15 µg/day (ingestion) 0.0005 µg/day (inhalation)	Yes.
2,2'-iminodiethanol	Yes.	No.	No.	No.

United States inventory (TSCA 8b) : Not determined.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

Canadian lists

Canadian NPRI : The following components are listed: Lead (and its compounds)


CEPA Toxic substances : The following components are listed: Lead

Canada inventory : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification :



International regulations

International lists :

- Australia inventory (AICS):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (ENCS):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory:** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.

15. Regulatory information

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Turkey inventory: Not determined.

**Chemical Weapons
Convention List Schedule
I Chemicals** : Not listed

**Chemical Weapons
Convention List Schedule
II Chemicals** : Not listed

**Chemical Weapons
Convention List Schedule
III Chemicals** : Listed

16. Other information

Label requirements : HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

**Hazardous Material
Information System (U.S.A.)** :

Health	2
Flammability	0
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection
Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

References : -Canada Gazette Part II, Vol. 122, No. 2 Registration SOR/88-64 31 December, 1987 Hazardous Products Act "Ingredient Disclosure List". -CFR29, OSHA's Permissible Exposure Limits, revision July, 1993. -CFR29, part 1910.1200, Hazard Communication. -CSST (Comission de Santé et Sécurité au Travail), document #RT-12: Classification of Certain Chemical Substances. -Material safety data sheet issued by: la Commission de la Santé et de la Sécurité du Travail du Québec. -NIOSH, Pocket Guide to Chemical Hazards, revision June 1994. -TSCA (Toxic Substance Contral Act), Chemical

16. Other information

Substance Inventory List, 1985.

Other special considerations : -OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). -The following component(s) of this product is(are) subject to the reporting requirements of section 313 of Title III of SARA (Superfund Amendments and Reauthorization Act, 1988) and 40 CFR Part 372: LEAD. -This product is not regulated as hazardous by DOT, IMO, or IATA. -TSCA (Toxic Substance Control Act): The components of this product are listed on the TSCA Inventory.

Date of printing : **10/14/2016**

Date of issue : 10/14/2016

Date of previous issue : No previous validation

Version : 0.01

Prepared by : C. Gosselin

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.